

Furniture with  
a mission.

**Soundwave<sup>®</sup>**

Original design, produced by Offecct.

OFFECCT

## THE ORIGINAL SOUNDWAVE® ACOUSTIC PANELS

It all started with Soundwave® Swell, designed by Teppo Asikainen in 1999. Man is influenced by all his senses, especially through the hearing and the sound around us. Offecct is constantly working to improve the sound environment in all our product development processes.

Read more at [offecct.com](https://offecct.com)

Case: Soundwave® Swell by Teppo Asikainen.  
Eckenberg Academy, Adelsheim, Germany.

# SOUNDWAVE® ACOUSTIC PANELS - STANDARD COLLECTION



## SOUNDWAVE® BELLA by 3XN

Bella is designed to be used as a sound absorber in the upper frequency range of 500 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite alt. upholstered in Europost	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.66	0.84 (incl. Basfill)
NRC	0.65*	0.85 (incl. Basfill)



## SOUNDWAVE® BOTANIC by Mario Ruiz

Botanic is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite alt. upholstered in Europost	
Size	H 585, W 585, D 62 (mm) H 23.03, W 23.03, D 2.44 (inches)	
SAA	0.81	0.90 (incl. Basfill)
NRC	0.80*	0.90 (incl. Basfill)



## SOUNDWAVE® CERAMIC by Thomas Sandell

Ceramic is designed to be used as a sound absorber in the upper frequency range of 500 Hz and above.

Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.74	
NRC	0.75*	




## SOUNDWAVE® FLO by Karim Rashid

Flo is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey, anthracite and fuchsia alt. upholstered in Europost	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.75	0.90 (incl. Basfill)
NRC	0.75*	0.90 (incl. Basfill)



## SOUNDWAVE® GEO by Ineke Hans

Geo is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.78	0.90 (incl. Basfill)
NRC	0.80*	0.90 (incl. Basfill)



## SOUNDWAVE® LUNA by Teppo Asikainen

Luna is designed to be used as a broadband absorber with extended efficiency in the low frequency range of 150 Hz-500 Hz.

Material	Recyclable moulded polyester fibre, back plate in PET	
Colour	Offwhite and grey	
Size	H 585, W 585, D 80 (mm) H 23.03, W 23.03, D 3.15 (inches)	
SAA	0.91	
NRC	0.90*	



## SOUNDWAVE® SCRUNCH by Teppo Asikainen

Scrunch is designed to be used as a sound absorber in the upper frequency range of 500 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite alt. upholstered in Europost	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.69	0.88 (incl. Basfill)
NRC	0.70*	0.90 (incl. Basfill)

\*Estimated NRC rating.




### SOUNDWAVE® SKY by Marre Moerel

Sky is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.73	0.89 (incl. Basfill)
NRC	0.75*	0.90 (incl. Basfill)




### SOUNDWAVE® STRIPES by Richard Hutten

Stripes is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 55 (mm) H 23.03, W 23.03, D 2.17 (inches)	
SAA	0.73	0.88 (incl. Basfill)
NRC	0.75*	0.90 (incl. Basfill)



### SOUNDWAVE® SWELL by Teppo Asikainen

Swell is designed to be used as a sound absorber in the frequency range of 250 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite alt. upholstered in Europost	
Size	H 585, W 585, D 90 (mm) H 23.03, W 23.03, D 3.54 (inches)	
SAA	0.75	0.89 (incl. Basfill)
NRC	0.75*	0.90 (incl. Basfill)




### SOUNDWAVE® SWELL DIFFUSER by Teppo Asikainen

Swell Diffuser is designed to provide sound diffusion rather than absorption. A diffuser helps spreading the sound energy evenly within rooms.

Please contact support for samples.

Material	100% PET	
Colour	Semi-transparent white	
Size	H 585, W 585, D 80 (mm) H 23.03, W 23.03, D 3.15 (inches)	



### SOUNDWAVE® VILLAGE by Claesson Koivisto Rune

Village is designed to be used as a sound absorber in the upper frequency range of 500 Hz and above.



Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.66	0.88 (incl. Basfill)
NRC	0.65*	0.90 (incl. Basfill)



### SOUNDWAVE® WICKER by Wingårdh & Wikerstål

Wicker is designed to be used as a sound absorber in the upper frequency range 500 Hz and above.

Material	Recyclable moulded polyester fibre	
Colour	Offwhite, grey and anthracite	
Size	H 585, W 585, D 60 (mm) H 23.03, W 23.03, D 2.36 (inches)	
SAA	0.67	
NRC	0.65*	



### SOUNDWAVE® PIX by Jean-Marie Massaud

Pix is designed to be used as a sound absorber in the upper frequency range of 150 Hz-500 Hz.

Please contact support for samples.



Material	Recyclable moulded polyester fibre	
Colour	Upholstered in Europost	
Size	H 290, W 146/290, D 290 (mm) H 11.42, W 5.75/11.42, D 11.42 (inches)	
SAA	0.66	
NRC	0.65*	

\*Estimated NRC rating.



### SOUNDWAVE® ANDO by Daniel Svahn

Ando is designed to be used as a broadband absorber with extended efficiency in the low frequency range of 150 Hz-500 Hz.

Material	Recyclable moulded polyester fibre with filling, basfill, made of recycled textile and PET
Colour	Grey RAL 7040
Size	H 1170, W 585, D 55 (mm) H 46.06, W 23.03, D 2.17 (inches)




### SOUNDWAVE® WALL by Christophe Pillet

Wall is designed to be used as a sound absorber in the upper frequency range of 500 Hz and above.

Material	Recyclable moulded polyester fibre
Colour	Offwhite
Size	H 2340, W 585, D 30 (mm) H 92.13, W 23.03, D 1.18 (inches)
SAA	0.38
NRC	0.40*

\*Estimated NRC rating.

## OPTIONAL ACCESSORIES



### BASFILL by Offecct Design Studio

Basfill is available as an option to all panels except for Ando, Ceramic, Luna, Pix, Swell Diffuser, Wall and Wicker.

Basfill is a filling material that when put inside the acoustic panel, adds sound absorbing qualities in the lower frequency range 150 Hz-500 Hz.

Material	40% reused textile, 20% reused PET and 40 % PET
Colour	Grey
Size	H 550, W 550, D 20 (mm) H 21.65, W 21.65, D 0.79 (inches)

## ADD COLOUR



### EUROPOST by Gabriel

Bella, Botanic, Flo, Pix, Scrunch and Swell can be upholstered in Europost.



OFFECCT

© Offecct AB, 2018. Tibro, Sweden, [offecct.com](http://offecct.com)